

Serial No. 09/937,367

RECEIVED
CENTRAL FAX CENTER
AUG 03 2006

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

LISTING OF CLAIMS:

1. (Canceled)
2. (Canceled)
3. (Canceled)
4. (Canceled)
5. (Canceled)
6. (Canceled)
7. (Canceled)
8. (Canceled)
9. (Canceled)
10. (Canceled)
11. (Canceled)
12. (Canceled)
13. (Canceled)
14. (Canceled)

Serial No. 09/937,367

15. (Canceled)

16. (Canceled)

17. (Canceled)

18. (Canceled)

19. (Canceled)

20. (Canceled)

21. (Canceled)

22. (Canceled)

23. (Currently Amended) The method according to claim 2243, wherein a discontinuity condition is signalled to an equipment management system.

24. (Previously Presented) The method according to claim 23, wherein signalled discontinuity condition information is stored in a transmission quality report.

25. (Canceled)

26. (Currently Amended) The method according to claim 2243, wherein the discontinuity condition detected at the first network element is transmitted within a defined data element of a virtual container transmitted to the second network element.

27. (Canceled)

28. (Currently Amended) The method according to claim 2243, wherein the discontinuity condition is signalled from the second network element to an equipment management system.

Serial No. 09/937,367

29. (Previously Presented) The method according to claim 28, wherein signalled discontinuity condition information is stored in a transmission quality report.

30. (Canceled)

31. (Currently Amended) The method according to claim 3043, wherein stepwise alteration comprises:

a pointer value adjustment towards a new valid pointer value; and
at each step, introduction of a pointer value difference which is within a standardized range of pointer increment or decrement operations.

32. (Previously Presented) The method according to claim 31, wherein the distance between a last valid pointer value before and the new valid pointer value after the detected discontinuity condition is used to evaluate and select a shortest difference for a stepwise adaptation of the pointer values.

33. (Previously Presented) The method according to claim 32 wherein, in case of similar differences for increasing or decreasing of the pointer value, the direction of pointer drift before the discontinuity condition occurred is used to determine a direction for the stepwise adaptation of the pointer values.

34. (Canceled)

35. (Currently Amended) The method according to claim 2243, wherein the first network element operates as a source network element and the second network element operates as a sink network element.

36. (Canceled)

37. (Canceled)

Serial No. 09/937,367

38. (Canceled)

39. (Canceled)

40. (Canceled)

41. (Canceled)

42. (Canceled)

43. (Currently Amended) A method of transmitting data in a synchronous hierarchic network system comprising at least a path segment between a first network element and at least a second network element on which tandem connection monitoring method is established for monitoring transmission of information over the path segment, the method comprising:

detecting frame offset discontinuities at the first network element on the basis of detection of an alteration of a pointer value;


wherein, after in response to detection of a frame offset discontinuity condition, transmitted pointer values are altered stepwise at the first network element,

wherein, during a time interval necessary for detection and transmission signalling to the second network element of a the frame offset discontinuity, a last valid pointer value received in advance of the discontinuity condition is transmitted to the second network element.

Serial No. 09/937,367

Respectfully,

By



Eugene J. Rosenthal, Attorney

Reg. No. 36,658

732-949-1857

Lucent Technologies Inc.

Date: 8/3/06